



M10 | Bifacial 108 cells (glass-glass type)

Power Output (STC): **415 - 435 Watt**
Max. Efficiency (STC): **22.28%**



High Mechanical Load

Certified to withstand high wind and snow loads up to 5400Pa



Enhanced Performances

Bifacial feature allows a power boost up to 20% vs monofacial



Lower LCOE

Higher power output over the long term increases projects ROI



Excellent Low-Light Performance

Tier 1 certified solar cells allows better performance in low-light environments



Ideal for Large Scale Installations

Lower installations time and BOS (Balance of Systems) costs




Salt Mist and Ammonia Resistant

Certified by Bureau Veritas to withstand usage near coastal environments



PID resistant

Designed to minimise cell degradation in extreme environments




Secure Investment

Upsolar provides exceptional product coverage for all modules to ensure our customers achieve superior long-term value from their solar installations. To further improve our product warranty, which covers unanticipated module damage, we've recently expanded our terms from a 10-year period to a 12-year period.

In addition, Upsolar offers a 30-year performance guarantee known as the Linear Module Warranty. Whereas traditional policies feature a single trigger point leading to drastic coverage reductions after just 10 years, Upsolar's coverage more accurately corresponds to system performance, providing coverage for over 30-years.

Overall, our goal is to deliver not only top-notch modules, but also peace of mind, for decades to come.



*Upsolar has expanded its manufacturing operations in Asia, Europe and North America, keeping its modules duty-free in the event of new CVD or AD policies. Please ask about pricing, payment terms and conditions to meet your needs.

Bifacial Series | Mono 182 108 cells

Electrical Characteristics at STC

STC: Irradiance 1,000 W/m², Module temperature 25°C, AM=1.5

MODEL	UP-B415MH-G (54M10)	UP-B420MH-G (54M10)	UP-B425MH-G (54M10)	UP-B430MH-G (54M10)	UP-B435MH-G (54M10)
Max Power P _m at STC (Wp)	415	420	425	430	435
Max Power Voltage V _m (V)	31.70	31.90	32.10	32.30	32.50
Max Power Current I _m (A)	13.09	13.17	13.24	13.31	13.38
Open-Circuit Voltage V _{oc} (V)	37.50	37.70	37.90	38.10	38.30
Short-Circuit Current I _{sc} (A)	14.14	14.21	14.28	14.35	14.42
Module Efficiency (STC)	21.25%	21.51%	21.76%	22.02%	22.28%
Bifacial Factor	0.70+/-0.05				

Bifacial Output-rearside Power Gain

5%	Max Power P _m (STC)	436	441	446	452	457
	Module Efficiency (STC)	22.31%	22.58%	22.85%	23.12%	23.39%
15%	Max Power P _m (STC)	477	483	489	495	500
	Module Efficiency (STC)	24.44%	24.73%	25.03%	25.32%	25.62%
25%	Max Power P _m (STC)	519	525	531	538	544
	Module Efficiency (STC)	26.57%	26.89%	27.21%	27.53%	27.85%

Components & Additional Data

Power tolerance	0/+3%
Front Glass	High Transparency Tempered Glass 0.078" // 2.0 mm
Junction Box	IP 68 or above
Output Cables	0.3m // IEC/ UL approved (4 mm ² , 12AWG) (PV Wire Type)
Connectors	MC4 compatible (IP67, IEC and UL approved)
Frame	Anodized aluminium alloy type 6063-T5
Encapsulation Material	EVA or POE
Back Sheet	High Transparency Tempered Glass 0.078" // 2.0 mm
Temperature Range	-40°F to +194°F // -40°C to +90°C
Series fuse rating	25A
Maximum system voltage	1,500V (IEC/UL)

Specifications


Cells	Monocrystalline bifacial solar cells 182 x 91
Number of Cells	108 (6 x 18)
Dimensions (in // mm)	67.791 x 44.64 x 1.18 // 1722 x 1134 x 30
Weight (lb // kg)	48.5 // 22.0

Temperature Coefficients

NMOT (°C)	45 ± 2
Temperature Coefficients of I _{sc} (% / °C)	0.05 ± 0.01
Temperature Coefficients of V _{oc} (% / °C)	-0.28 ± 0.02
Temperature Coefficients of I _m (% / °C)	-0.02 ± 0.02
Temperature Coefficients of V _m (% / °C)	-0.42 ± 0.03
Temperature Coefficients of P _m (% / °C)	-0.35 ± 0.05


IV Curves

PV module: Upsolar, UP-B435MH-G(54M10)




Options Available

Frameless option available
Transparent backsheet option available



Section B-B
8:1



Section A-A
8:1

