



166 Monocrystalline Half-Cut 72 cells

Power Output: **435 - 455 Watt**
Max. Efficiency: **20.4%**



High Mechanical Load

Certified to withstand high wind and snow loads up to 5400Pa



Enhanced Performance

Half cut cell feature allows a power increase of at least 5Wp vs. standard modules



Anti-reflective Surface

Increases the panel's exposure and efficiency of converting sunlight into energy



Lower Hot Spots

Half cut design reduces energy loss caused by shading between modules



Ideal for Large Scale Installations

Lower installations time and BOS (Balance of Systems) costs



Salt Mist and Ammonia Resistant

Certified by Bureau Veritas to withstand usage near coastal environments



PID free

Designed to minimise cell degradation in extreme environments




Secure Investment

Upsolar provides exceptional product coverage for all modules to ensure our customers achieve superior long-term value from their solar installations. To further improve our product warranty, which covers unanticipated module damage, we've recently expanded our terms from a 10-year period to a 12-year period.

In addition, Upsolar offers a 25-year performance guarantee known as the Linear Module Warranty. Whereas traditional policies feature a single trigger point leading to drastic coverage reductions after just 10 years, Upsolar's coverage more accurately corresponds to system performance, providing coverage for over 25 years.

Overall, our goal is to deliver not only top-notch modules, but also peace of mind, for decades to come.



*Upsolar has expanded its manufacturing operations in Asia, Europe and North America, keeping its modules duty-free in the event of new CVD or AD policies. Please ask about pricing, payment terms and conditions to meet your needs.

Mono 166 | Half-Cut 72 cells

Electrical Characteristics

MODEL	UP-M435MH	UP-M440MH	UP-M445MH	UP-M450MH	UP-M455MH
Max Power Pm (Wp)	435	440	445	450	455
Max Power Voltage Vm (V)	40.6	40.8	41.0	41.2	41.4
Max Power Current Im (A)	10.71	10.78	10.85	10.92	10.99
Open-Circuit Voltage Voc (V)	49.4	49.6	49.8	50.0	50.2
Short-Circuit Current Isc (A)	11.33	11.40	11.47	11.54	11.61
Module Efficiency	19.5%	19.7%	20.0%	20.2%	20.4%
Maximum System Voltage (V)	1000(IEC)/1000(UL) or 1500(IEC)/1500(UL)				
Power Tolerance	0/+3%				
Series Fuse Rating (A)	20A				

STC: Irradiance 1000 W/m², Module temperature 25°C, AM=1.5

Components & Mechanical Data

Front Glass	High Transparency Tempered Glass 0.125" // 3.2 mm
Junction Box	IP 68
Bypass Diode	3 diodes
Output Cables	IEC, UL approved (4 mm ² , 12AWG) (PV Wire Type)
Connectors	MC4 compatible (IP67, IEC and UL approved)
Frame	Anodized aluminium alloy type 6063-T5
Encapsulation Material	EVA
Back Sheet	White multilayer polymer film
Temperature Range	-40°F to +194°F // -40°C to +90°C
Max Load	75 lbs / ft ² (UL Standard) // 5400 Pa (IEC Standards)
Impact Resistance	Steel ball - 1.18 lbs // 535 g dropped from 51" // 1.3 m high


Specifications

Cells	Mono PERC 166 x 83
Number of Cells	144 (6 x 24)
Dimensions (in // mm)	83.00 x 41.28 x 1.37 // 2115 x 1052 x 35
Weight (lb // kg)	52.9 // 24.0

Temperature Coefficients

NOCT (°C)	43 ± 2
Temperature Coefficients of Isc (% / °C)	0.048 ± 0.01
Temperature Coefficients of Voc (% / °C)	-0.30 ± 0.02
Temperature Coefficients of Im (% / °C)	-0.02 ± 0.02
Temperature Coefficients of Vm (% / °C)	-0.40 ± 0.03
Temperature Coefficients of Pm (% / °C)	-0.38 ± 0.05

IV Curves



Options Available

Black or transparent backsheet
Customized cable length

